

### decolith **woodstain**

## DECOLITH WOODSTAIN

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name Product Description

Manufacturer

Head Office

Emergency Phone Number

Fax Numbers

**DECOLITH WOODSTAIN** 

Paint

PT. WARNA AGUNG

Komplek Delta Building Jl. Suryopranoto 1 - 9 No. C 3-6

Jakarta 10160

(021) 5918746

(021) 5918745

#### 2. HAZARDS IDENTIFICATION

#### **Physical Hazard**

Flammable Hazard Category 0

#### **Health Hazard**

**GHS Pictogram** 

Skin corrosion/irritation Category 0
Serious eye damage/irritation Category 1
Skin sensitization Category 1

Specific target organ toxicity:

- Repeated exposure

#### **Hazard statements**

Category 0



H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances CAS Number Concentration (%w/w)
Water 7732-18-5 10 - 20%

Mixture of Micro Biocides
Acrylic Copolymer Dispersion

Not Applicable

50 - 70%

3-lodo-2-propynyl butyl carbamate 55406-53-6 **0.5 - 3.0%** 

Halaman 1/4



Number : STD-R&D-036b Rev 00 Effective Date : 27 / 08 / 2024



## decolith woodstain

## **DECOLITH WOODSTAIN**

#### 4. FIRST AID MEASURES

Description of first aid measures

Skin Contact

Eye Contact

Inhalation

Ingestion

Wash thoroughly with soap and water. Remove contaminated clothing and wash it before re-use. Consult a physician If irritation persists.

Flush immediately with large amount of water, especially under lids for at least 15 minutes. Consult a physician If irritation persists.

Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort.

If swallowed, obtain medical treatment immediately.

#### **5. FIRE-FIGHTING MEASURES**

Flammability of the product
Flash Points
Fire Extinguishing Media
Products of Combustion
Unusual Fire and Explosion hazards

Not Applicable. Not Applicable.

Use Dry Chemical, Alcohol Foam, Carbon Dioxide.
Carbon Dioxide, carbon monoxide, other irritating gases.
Closed containers may explode (due to the build-up of pressure)
when exposed to extreme heat. During emergency conditions
overexposure to decomposition products may cause a health hazard.

#### **6. ACCIDENTAL RELEASE MEASURES**

#### Personal Precautions, Protective Equipment And Emergency Procedure

Appropriate protective equipment must be worn when handling a spill of this material. If exposed to material during clean- up operation, see SECTION 4, for actions to follow.

#### Methods And Materials For Containments And Cleaning Up

Collect wet material using a scoop. Scrape up and place in appropriate containers for recovery or disposal.

#### 7. HANDLING AND STORAGE

Precautions For Safe Handling

Keep product in dry place (below 38°C), good ventilation, and restrain from UV light and high temperature directly. Do not eat, drink or smoke, when handling. Wash hands with soap and water after handling especially before eating or smoking. Avoid physical damage of container.

#### Other Precautions

Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Keep containers tightly closed and upright when not in use.

Halaman 2/4



Number : STD-R&D-036b Rev 00 Effective Date : 27 / 08 / 2024



### decolith woodstain

## **DECOLITH WOODSTAIN**

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Precautions to be taken in use Use only with adequate ventilation. Avoid contact with skin and

eyes. Avoid Breathing vapor and spray mist. Wash hands after

using water.

Ventilation Provide dilution ventilation or local exhaust to prevent build-up

of vapors.

Personal protective equipment Eye wash, safety shower, safety glasses or goggles. Impervious

gloves, impervious clothing.

General Hygiene Practice Wash after handling. Prevent eye contact. Avoid prolonged skin

and Inhalation contact.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid

Color Transparent Color Solubility in water Soluble in water

Odor Characteristic
Viscosity
Density at 30°C
Boiling Point
Slight
70 KU
1,05 Kg/L
100°C

#### 10. STABILITY AND REACTIVITY

Hazardous polymerization

Stability These products are stable, not reactive.

Condition to avoid Avoid contact with high temperature, freezing, open flame.

Incompatibility As such it is incompatible with acids and oxidizers.

Will not occur.

#### 11. TOXICOLOGICAL INFORMATION

Toxicity Mercury and Lead Free.

Dry film is nontoxic.

#### 12. ECOLOGICAL INFORMATION

Ecotoxicity No Applicable Data.

General Note Do not allow undiluted product or large quantities of products to

reach ground water, water courses or sewage systems.

Halaman 3/4

Effective Date : 27 / 08 / 2024

Number: STD-R&D-036b Rev 00







## **DECOLITH WOODSTAIN**

#### 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable regulations ensuring no contamination of surrounding environment.

#### 14. TRANSPORT INFORMATION

Freight Classification Shipping Name

Packing Group Identification Number Paint Products.

Not dangerous goods.

Not special transportation requirements.

None.

Not applicable.

#### 15. REGULATORY INFORMATION

This product is not classified as hazardous product base on Indonesian Regulation.

#### 16. OTHER INFORMATION

#### Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.

Halaman 4/4



Number : STD-R&D-036b Rev 00 Effective Date : 27 / 08 / 2024