

Material Safety Data Sheet

permacoat[®] MATTE FINISH

PERMACOAT MATTE FINISH

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name Product Description Manufacturer Head Office PERMACOAT MATTE FINISH Paint PT. WARNA AGUNG Komplek Delta Building Jl. Suryopranoto 1 - 9 No. C 3-6 Jakarta 10160 (021) 5918746 (021) 5918745

Emergency Phone Number Fax Numbers

2. HAZARDS IDENTIFICATION

Physical Hazard

Flammable Hazard

Health Hazard

Skin corrosion/irritation Serious eye damage/irritation Skin sensitization Specific target organ toxicity: - Repeated exposure

GHS Pictogram



Category 0

Category 0 Category 1 Category 1

Category 0

Hazard statements

- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation.
- H411: Toxic to aquatic life with long lasting effects.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Substances	CAS Number	Concentration (%w/w)
Water	7732-18-5	20 - 30%
Titanium Dioxide	13463-67-7	10 - 20%
Limestone	1317-65-3	10 - 25%
Acrylic Copolymer Dispersion		20 - 30%
Mixture of 5-chloro-2-methyl-2H-	55965-84-9	0.1 - 2%
isothiazol-3-one and 2-methyl-2H-		
isothiazol-3-one		

Halaman 1/4





Material Safety Data Sheet

permacoat[®] MATTE FINISH

PERMACOAT MATTE FINISH

4. FIRST AID MEASURES

Description of first aid measures Skin Contact

Eye Contact

Inhalation

Ingestion

5. FIRE-FIGHTING MEASURES

Flammability of the product Flash Points Fire Extinguishing Media Products of Combustion Unusual Fire and Explosion hazards Wash thoroughly with soap and water. Remove contaminated clothing and wash it before re-use. Consult a physician If irritation persists. Flush immediately with large amount of water, especially under lids for at least 15 minutes. Consult a physician If irritation persists. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort. If swallowed, obtain medical treatment immediately.

Not Applicable. Not Applicable. Use Dry Chemical, Alcohol Foam, Carbon Dioxide. Carbon Dioxide, carbon monoxide, other irritating gases. Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment And Emergency Procedure

Appropriate protective equipment must be worn when handling a spill of this material. If exposed to material during clean- up operation, see SECTION 4, for actions to follow.

Methods And Materials For Containments And Cleaning Up

Collect wet material using a scoop. Scrape up and place in appropriate containers for recovery or disposal.

7. HANDLING AND STORAGE

Precautions For Safe Handling

Keep product in dry place (below 38°C), good ventilation, and restrain from UV light and high temperature directly. Do not eat, drink or smoke, when handling. Wash hands with soap and water after handling especially before eating or smoking. Avoid physical damage of container.

Other Precautions

Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Keep containers tightly closed and upright when not in use.

Halaman 2/4



Number : STD-R&D-040b Rev 00 Effective Date : 27 / 08 / 2024



Material Safety Data Sheet

permacoat MATTE FINISH

PERMACOAT MATTE FINISH

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Precautions to be taken in use

Ventilation

Personal protective equipment

General Hygiene Practice

Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid Breathing vapor and spray mist. Wash hands after using water. Provide dilution ventilation or local exhaust to prevent build-up of vapors. Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing. Wash after handling. Prevent eye contact. Avoid prolonged skin

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Solubility in water Odor Characteristic Viscosity Density at 30°C Boiling Point Liquid Various Soluble in water Slight 90 - 95 KU 1,30 - 1,45 g/cm³ Not available

and Inhalation contact.

10. STABILITY AND REACTIVITY

Stability Condition to avoid Incompatibility Hazardous polymerization These products are stable, not reactive. Avoid contact with high temperature, freezing, open flame. As such it is incompatible with acids and oxidizers. Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicity

Mercury and Lead Free. Dry film is nontoxic.

12. ECOLOGICAL INFORMATION

Ecotoxicity General Note No Applicable Data. Do not allow undiluted product or large quantities of products to reach ground water, water courses or sewage systems.

Halaman 3/4





permacoat MATTE FINISH

PERMACOAT MATTE FINISH

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable regulations ensuring no contamination of surrounding environment.

14. TRANSPORT INFORMATION

Freight Classification Shipping Name

Packing Group Identification Number Paint Products. Not dangerous goods. Not special transportation requirements. None. Not applicable.

15. REGULATORY INFORMATION

This product is not classified as hazardous product base on Indonesian Regulation.

16. OTHER INFORMATION

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.

Halaman 4/4

